

Specification Guide - ASI-X Packer

Casing		Casing I.D. Range (IN.)		Packer O.D. (IN.)	Packer I.D. (IN.)	Thread Connection Box up/Pin down	Part Number
O.D. (IN.)	Weight (LBS./FT.)	Min.	Max.				
2-7/8	6.4-6.5	2.441	2.441	2.25	0.63	1.050 EUE	60325
3-1/2	7.7-10.2	2.922	3.068	2.781	1.25	1.900 NU	60335
3-1/2	12.95	2.750	2.75	2.562	1.00	1.660 EUE	60336
4	9.5-11	3.476	3.548	3.250	1.50	1.900 EUE	60340
4	12.95	3.340	3.340	3.187	1.50	1.900 EUE	60341
4-1/2	18.8	3.640	3.640	3.437	1.50	1.900 EUE	60342
4-1/2	15.1-16.9	3.740	3.826	3.594	1.50	1.900 EUE	60343
4-1/2	15.1	3.826	3.826	3.656	1.94	2-3/8 EUE	60344
4-1/2	9.5-13.5	3.920	4.090	3.750	1.94	2-3/8 EUE	60345
4-1/2	15.1	3.826	3.826	3.641	1.94	2-3/8 EUE	60346
5	11.5-15	4.408	4.560	4.125	1.94	2-3/8 EUE	60350
5	18-20.8	4.156	4.276	4.000	1.94	2-3/8 EUE	60352
5-1/2	14-20	4.778	5.044	4.625	2.00	2-3/8 EUE	60355
5-1/2	15.5-17	4.892	4.95	4.625	2.38	2-7/8 EUE	60356
5-1/2	20-23	4.670	4.778	4.500	2.00	2-3/8 EUE	60357
5-1/2	13-14	5.012	5.044	4.813	2.38	2-7/8 EUE	60358
5-1/2	20-23	4.670	4.778	4.500	2.38	2-7/8 EUE	60359
6	17-20	5.352	5.450	5.188	2.38	2-7/8 EUE	60360
6	14-16	5.500	5.552	5.188	2.38	2-7/8 EUE	60361
6-5/8	24-32	5.675	5.920	5.500	2.50	2-7/8 EUE	60365
6-5/8	32-34.5	5.575	5.675	5.312	2.50	2-7/8 EUE	60366
6-5/8	17-24	5.921	6.135	5.750	2.50	2-7/8 EUE	60367
6-5/8	20-24	5.921	6.049	5.750	3.00	3-1/2 EUE	60368
6-5/8	20	6.049	6.049	5.812	3.00	3-1/2 EUE	60369
7	26-32	6.094	6.276	5.875	2.50	2-7/8 EUE	60370
7	29-35	6.004	6.184	5.812	2.50	2-7/8 EUE	60371
7	17-26	6.276	6.538	6.062*	2.50	2-7/8 EUE	60372
7	26-32	6.094	6.276	5.875	3.00	3-1/2 EUE	60373
7	17-26	6.276	6.538	6.125*	3.00	3-1/2 EUE	60374
7-5/8	24-29.7	6.875	7.025	6.672	2.50	2-7/8 EUE	60375
7-5/8	33.7-39	6.625	6.765	6.453	2.50	2-7/8 EUE	60376
7-5/8	33.7-39	6.625	6.765	6.453	3.00	3-1/2 EUE	60377
7-5/8	24-29.7	6.875	7.025	6.672	3.00	3-1/2 EUE	60378
8-5/8	28-40	7.725	8.017	7.500	4.00	4-1/2 EUE	60382
8-5/8	24-40	7.725	8.097	7.500	2.50	2-7/8 EUE	60385
8-5/8	44-49	7.511	7.625	7.312	2.50	2-7/8 EUE	60386
8-5/8	28-40	7.725	8.017	7.500	3.00	3-1/2 EUE	60387
9-5/8	43.5-53.5	8.535	8.755	8.250	4.00	4-1/2 EUE	60395
9-5/8	32.3-43.5	8.755	9.001	8.500	4.00	4-1/2 EUE	60396
10-3/4	32.75-45.5	9.560	10.192	9.700	4.00	4-1/2 EUE	60301
10-3/4	45.5-51	9.85	9.95	9.625	4.00	4-1/2 EUE	60302
10-3/4	51-65.7	9.560	9.850	9.312	4.00	4-1/2 EUE	60310
11-3/4	42-65.0	10.682	11.084	10.438	4.00	4-1/2 EUE	60311
13-3/8	54.5-77	12.275	12.615	12.00	4.00	4-1/2 EUE	60313

* Maximum O.D. is across retracted drag blocks. ** Other sizes and connections available on request