



INTERNATIONAL LIFT SYSTEMS, L.L.C.

Specification Guide - Casing Packer

Casing		Tubing/ Casing (IN)	Casing Range (IN.)		Packer O.D. (IN.)	Packer I.D. (IN.)	Thread Connection Box up/Pin down	Part Number
O.D. (IN.)	Weight (LBS./FT.)		Min.	Max.				
4-1/2	9.5-13.5		2-7/8	3.920				
5	11.5-20.3	2-7/8	4.184	4.560	4.000	2.50	2-7/8 EUE	44050
5-1/2	13-20	3-1/2	4.778	5.044	4.625	3.00	3-1/2 EUE	44055
5-1/2	13-17	4	4.892	5.044	4.650	3.50	4 NU	44056
5-3/4	14-17	4	5.190	5.290	4.875	3.50	4-1/2 EUE	44057
6	18-20	4	5.352	5.424	5.188	3.50	4 EUE	44060
6-5/8	20-28	4-1/2	5.791	6.049	5.625	4.00	4-1/2 LTC	44065
7	17-38	4-1/2	5.920	6.538	5.750	4.00	4-1/2 LTC	44070
7	20-29	5	6.184	6.456	5.969	4.50	5 LTC	44071
7-5/8	20-33.7	4-1/2	6.765	7.125	6.500	4.00	4-1/2 LTC	44075
7-5/8	20-33.7	5-1/2	6.765	7.125	6.500	5.00	5-1/2 LTC	44076
8-5/8	24-40	4-1/2	7.725	8.097	7.500	4.00	4-1/2 LTC	44084
8-5/8	24-40	5-1/2	7.725	8.097	7.500	5.00	5-1/2 LTC	44085
8-5/8	24-36	6-5/8	7.825	8.097	7.656	6.00	6-5/8 LTC	44086
8-5/8	24-36	7	7.825	8.097	7.656	6.50	7 LTC	44087
9-5/8	32.3-43.5	7	8.755	9.001	8.500	6.50	7 LTC	44095
10-3/4	32.7-55.5	7	9.760	10.192	9.500	6.50	7 LTC	44010
11-3/4	42-65	8-5/8	10.682	11.084	10.500	8.00	8-5/8 LTC	44011
13-3/8	48-77	9-5/8	12.275	12.715	12.000	8.75	9-5/8 LTC	44013
18-5/8	87.5-117.5	13-3/8	17.439	17.755	17.000	12.50	13-3/8 LTC	44018

©INTERNATIONAL LIFT SYSTEMS, L.L.C.

* Other sizes and connections available on request