



INTERNATIONAL LIFT SYSTEMS, L.L.C.

Specification Guide - Set Down Isolation Packer

Casing		Casing Range (IN.)		Packer O.D. (IN.)	Packer I.D. (IN.)	Thread Connection	Part Number
O.D. (IN.)	Weight (LBS./FT.)	Min.	Max.			Box up/Pin down	
2-7/8	6.5	2.441	2.441	2.250	1.500	1.900 NU	64127
4-1/2	9.5-13.5	3.920	4.090	3.750	1.938	2-3/8 EUE	64145
5	11.5-18	4.276	4.560	4.000	1.938	2-3/8 EUE	64150
5-1/2	13-20	4.778	5.044	4.625	2.430	2-7/8 EUE	64156
5-1/2	13-20	4.778	5.044	4.625	1.938	2-3/8 EUE	64155
5-1/2	13-20	4.778	5.044	4.625	3.000	3-1/2 EUE	64158
7	17-26	6.276	6.538	6.000	2.430	2-7/8 EUE	64170
7	17-26	6.276	6.538	6.000	2.000	2-3/8 EUE	64171
7	32-35	6.004	6.094	5.750	4.000	4-1/2 8RD	64172
7	26-32	6.094	6.276	5.875	3.000	3-1/2 EUE	64173
7	17-26	6.276	6.538	6.000	3.000	3-1/2 EUE	64174
7-5/8	24-29.7	6.875	7.025	6.625	2.430	2-7/8 EUE	64175
9-5/8	40-47	8.681	8.835	8.438	4.000	4-1/2 EUE	64195
9-5/8	40-47	8.681	8.835	8.438	3.000	3-1/2 EUE	64196

* Other sizes and connections available on request